

Dewsbury & Proud Ltd

Contract Lifting & Crane Hire Specialists

MRT4 Dual Circuit [320kg]

The MRT4, with dual-circuit vacuum system technology for extra safety, is built for versatility. It delivers 360° rotation with 90° tilt from any rotation position. Using the extension arms and movable pads, three frame configurations are possible to cover most load sizes on site or in the workshop. A variable length lifting arm may be specified, allowing fitting under soffits and overhangs.

•Dual, independent vacuum circuits with two vacuum reserve tanks and two non-return valves

•Vacuum gauge for each circuit

•Manual 360° lockable rotation (continuous)

•Manual tilting from vertical to horizontal

•On-board maintenance-free vacuum pump

•12v rechargeable battery with integral 110v or 240v charger and battery energy gauge

•Audio-visual low vacuum alert

•Four extension arms allow alternative configurations



Technical Specifications

S Extra Frame Configurations

Vacuum system	dual circuit	1 pump, 2 vacuum tanks
Suitable for lifting	material properties:	gastight
	surface:	smooth
	example:	glass, plastic boards, ceramic plates, sheet metals, coated board
Suction cup type	approx diameter.	305mm
Suction cup quality	description:	black rubber, not abrasion resistant, heat resistant up to 100°C
Number of suction cups	cups:	4
Loading capacity	vertical:	320kg
of frame	horizontal:	320kg
Weight of lifter	approx	58kg
Structural depth	approx	292mm
Output	approx	1.5m³/h
Voltage	pump:	12v DC from rechargeable battery
	battery charger.	110v/240v 50/60Hz single phase factory selectable
Standard accessories	standard:	4 x extension arms
Optional accessories	optional:	variable length lifting arm, extra length extension arms