



## TRACKED CARRIER- (1200 R)

### FEATURES

**R**  
MODEL

|  |   |
|--|---|
| Efficient direct AC electric drive       | ● |
| Fully proportional remote control        | ● |
| Maintenance free AGM batteries           | ● |
| Hazard lights front and rear             | ● |
| Switchable motion alarm                  | ● |
| On board diagnostics                     | ● |
| Adaptable and extendable platform        | ● |
| LCD information screen on remote control | — |
| Smart auxiliary output socket            | — |
| Automatic gradient/speed monitoring      | — |
| Non-marking tracks                       | ○ |
| Wide range of accessories                | ○ |

○ = Optional    ● = As Standard



The 1200 series from Dewsbury & Proud the ideal all-round carrier. At just 750mm wide the 1200 R can fit through most doorways, and with a substantial 1,200kg maximum capacity the uses are endless. R models use state-of-the-art technology whilst being simple to operate, reliable and easy to maintain.

### DIMENSIONS

|                            |        |
|----------------------------|--------|
| Width overall (A)          | 750mm  |
| Width of bed (B)           | 740mm  |
| Length of bed/overall (C)  | 1120mm |
| Length extended (D)        | 1700mm |
| Height (E)                 | 360mm  |
| Track width (F)            | 150mm  |
| Track length on ground (G) | 800mm  |
| Ground clearance (centre)  | 60mm   |

### CAPACITIES

|                              |        |
|------------------------------|--------|
| Max capacity on level ground | 1200kg |
| Max capacity at max gradient | 300kg  |
| Max gradient                 | 45°    |
| Max side slope               | 30°    |
| Max speed                    | 3km/h  |
| Unladen weight               | 340kg  |

### POWER

|                  |           |
|------------------|-----------|
| Power (max)      | 2.4kW     |
| Voltage          | 24V       |
| Battery capacity | 115Ah     |
| Charger input    | 110V-230V |

