



## 1m x 1m CRANE OUTRIGGER MATS

**Four Individual Mats = 1m x 1m  
With a 1m Coverage Area**



**Delivered By Transport and Individually  
Lifted into Position by Two people or onsite forklift**

- Fully Certified
- 4 individual mats per set
- Length 1m
- Width 1m
- Thickness 80mm
- Max Individual mat weight = 77kg
- Max Point Load = 105,000kg

### Applications

- ✓ Crane Outriggers
- ✓ Concrete Pumps
- ✓ MEWPS
- ✓ Scissor Lifts







- **Ideal for:** Mewps, Small mobile cranes, Plant Equip, RT Booms, Spider Lifts, Van Mounted Platforms, HIABS, Truck mounted cranes, Small mobile cranes.
- **Colour:** Confetti
- **Dimensions(L x W x H)**  
mm: 1000x1000x80
- **Weight (kg):** 77.00
- **Material:** Made from extremely high quality, UHMW-PE (Ultra High Molecular Weight Polyethylene)
- **Load capacity (tonnes):** 105.00
- **Resistant to:** Oil, Water, Chemicals, Corrosion and Splintering
- Easy to handle and store with minimal effort



## DATA SHEET

# PREMIUM OUTRIGGER PAD

High performance outrigger pads that provide incredible strength and rigidity with excellent load distribution. Ideal for use with small equipment through to heavy-duty lifting applications.

- Engineered from Ultra High Molecular Polyethylene (UHMW-PE)
- Resistant to water, oil & chemicals
- Lightweight and easy to handle
- Carry, position and store with minimal effort

SUITABLE FOR:

