



2.5m x 1.4m CRANE OUTRIGGER MATS

**Four Individual Mats = 2.5m x 1.4m
With a 3.5m Coverage Area**



**Delivered By Transport and Individually
Lifted into Position by the crane or onsite forklift**

- Fully Certified
- 4 individual mats per set
- Length 2.5m
- Width 1.4m
- Thickness 100mm
- Max Individual mat weight = 300kg
- Max Point Load = 120,000kg

Applications

- ✓ Crane Outriggers
- ✓ Concrete Pumps
- ✓ MEWPS

- ✓ Scissor Lifts





NEED ADVICE?

We have experienced staff who can help you. We can visit your site to discuss your needs.

+44 (0) 1902 405553

- **Ideal for:** Mewps, Small mobile cranes, Plant Equip, RT Booms, Spider Lifts, Van Mounted Platforms, HIABS, Truck mounted cranes, Small mobile cranes.
- **Colour:** Confetti
- **Dimensions(L x W x H)**
mm: 2500x1400x100
- **Weight (kg):** 300.00
- **Material:** Made from extremely high quality, UHMW-PE (Ultra High Molecular Weight Polyethylene)
- **Load capacity (tonnes):** 120
- **Resistant to:** Oil, Water, Chemicals, Corrosion and Splintering
- Easy to handle and store with minimal effort

DATA SHEET

PREMIUM OUTRIGGER PAD

High performance outrigger pads that provide incredible strength and rigidity with excellent load distribution. Ideal for use with small equipment through to heavy-duty lifting applications.

- Engineered from Ultra High Molecular Polyethylene (UHMW-PE)
- Resistant to water, oil & chemicals
- Lightweight and easy to handle
- Carry, position and store with minimal effort

SUITABLE FOR:

